

NANLITE

PavoSlim 60B/120B/240B DMX REFERENCE GUIDE

This DMX reference guide has been compiled according to the rigorous testing of Nanlite product. Product designs are subject to change without prior notice. The latest version of the DMX reference guide for this product is downloadable at www.nanlite.com.

CCT 8bit

CHANNEL	VALUE	%	FUNCTION	NOTES
1	0-255	0-100	DIMMER 0.0% to 100.0%	
2	0-255	0-100	CCT 2700K - 6500K	

When "DMX Reduced Channels" is ON, the following channels are reduced in all DMX modes except ULTIMATE DMX MODE.

CHANNEL	VALUE	%	FUNCTION	NOTES
3	0 - 3 4 5 6 7-255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	STROBE OFF Random Fast Random Medium Random Slow Variable Strobe(0.4Hz --> 25Hz)	
4 - 5			RESERVED	

ULTIMATE DMX 8bit - CCT MODE

CHANNEL	VALUE	%	FUNCTION	NOTES
1	0-255	0-100	DIMMER 0.0% to 100.0%	
2	0-63 64-127 128-255	0-25 26-50 51-100	MODE CCT EFFECT RESERVED	$0 \leq \text{value} \leq 63$
3	0-255	0-100	CCT 2700K - 6500K	
4-10			N/A	

ULTIMATE DMX 8bit - EFFECT MODE

CHANNEL	VALUE	%	FUNCTION	NOTES
1	0-255	0-100	DIMMER 0.0% to 100.0%	
2	0-63 64-127 128-255	0-25 26-50 51-100	MODE CCT EFFECT RESERVED	64 ≤ value ≤ 127
3	0-18 19-36 37-54 55-72 73-90 91-108 109-126 127-144 145-162 163-180 181-198 199-216 217-255	0-7 8-14 15-21 22-28 29-35 36-42 43-50 51-57 58-64 65-71 72-78 79-85 86-100	EFFECT MODE CCT LOOP INT LOOP FLASH PULSE STORM TV PAPARAZZI CANDLE/FIRE BAD BULB FIREWORK EXPLOSION WELDING RESERVED	
4	0-255	0-100	DMX EFFECTS PARAMETER #1	See DMX Effects chart
5	0-255	0-100	DMX EFFECTS PARAMETER #2	See DMX Effects chart
6	0-255	0-100	DMX EFFECTS PARAMETER #3	See DMX Effects chart
7	0-255	0-100	DMX EFFECTS PARAMETER #4	See DMX Effects chart

ULTIMATE DMX 8bit - EFFECT MODE

CHANNEL	VALUE	%	FUNCTION	NOTES
8	0-255	0-100	DMX EFFECTS PARAMETER #5	See DMX Effects chart
9	0-255	0-100	DMX EFFECTS PARAMETER #6	See DMX Effects chart
10	0-255	0-100	DMX EFFECTS PARAMETER #7	See DMX Effects chart

DMX EFFECT CHART

EFFECT	CCT LOOP 0 ≤ value ≤ 18			
CH4/PARAMETER #1	CCT 1			
CH5/PARAMETER #2	CCT 2			
CH6/PARAMETER #3	SPEED			
CH7/PARAMETER #4	CYCLE:ONE WAY = 0-85(0%-33%) CYCLE:TWO WAY = 86-170(34%-66%) CYCLE:REVERSE = 171-255(67%-100%)			
CH8/PARAMETER #5	ADD-ON:OFF = 0-63(0%-25%)	ADD-ON:FLASH = 64-127(26%-50%)	ADD-ON:RANDOM FLASH = 128-191(51%-75%)	ADD-ON:PULSE = 192-255(76%-100%)
CH9/PARAMETER #6	N/A	INTERVALS	SPEED	PULSES/MIN
CH10/PARAMETER #7	N/A	FLASH RATIO	N/A	N/A

DMX EFFECT CHART

EFFECT	INT LOOP 19 ≤ value ≤ 36			
CH4/PARAMETER #1	DIM LOW			
CH5/PARAMETER #2	CCT			
CH6/PARAMETER #3	SPEED			
CH7/PARAMETER #4	CYCLE:ONE WAY = 0-85(0%-33%) CYCLE:TWO WAY = 86-170(34%-66%) CYCLE:REVERSE = 171-255(67%-100%)			
CH8/PARAMETER #5	ADD-ON:OFF = 0-63(0%-25%)	ADD-ON:FLASH = 64-127(26%-50%)	ADD-ON:RANDOM FLASH = 128-191(51%-75%)	ADD-ON:PULSE = 192-255(76%-100%)
CH9/PARAMETER #6	N/A	INTERVALS	SPEED	PULSES/MIN
CH10/PARAMETER #7	N/A	PULSES/MIN	N/A	N/A

DMX EFFECT CHART

EFFECT	FLASH 37 ≤ value ≤ 54	
CH4/PARAMETER #1	CCT	
CH5/PARAMETER #2	INTERVALS	
CH6/PARAMETER #3	FLASH RATIO	
CH7/PARAMETER #4	PAUSE: OFF = 0-127(0%-50%)	PAUSE: ON = 128-255(51%-100%)
CH8/PARAMETER #5	N/A	
CH9/PARAMETER #6	N/A	
CH10/PARAMETER #7	N/A	

DMX EFFECT CHART

EFFECT	PULSE 55 ≤ value ≤ 72
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	PULSES/MIN
CH6/PARAMETER #3	N/A
CH7/PARAMETER #4	N/A
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	STORM 73 ≤ value ≤ 90
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	FLASH TIMES HIGH
CH6/PARAMETER #3	FLASH TIMES LOW
CH7/PARAMETER #4	TRIGGER: AUTO = 0-127(0%-50%)
CH8/PARAMETER #5	TRIGGER: MANUAL = 128-255(51%-100%)
CH9/PARAMETER #6	INTERVAL HIGH
CH10/PARAMETER #7	INTERVAL LOW
	Trigger: OFF = 0-127(0%-50%)
	Trigger: ON = 128-255(51%-100%)
	N/A
	PAUSE: OFF = 0-127(0%-50%)
	PAUSE: ON = 128-255(51%-100%)
	N/A

DMX EFFECT CHART

EFFECT	TV 91 ≤ value ≤ 108
CH4/PARAMETER #1	DIM LOW
CH5/PARAMETER #2	CCT
CH6/PARAMETER #3	CCT SHIFT
CH7/PARAMETER #4	SPEED
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	PAPARAZZI 109 ≤ value ≤ 126
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	SPEED
CH6/PARAMETER #3	N/A
CH7/PARAMETER #4	N/A
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	CANDLE/FIRE 127 ≤ value ≤ 144
CH4/PARAMETER #1	DIM LOW
CH5/PARAMETER #2	CCT
CH6/PARAMETER #3	CCT SHIFT
CH7/PARAMETER #4	SPEED
CH8/PARAMETER #5	FLICKER: OFF = 0-127(0%-50%) FLICKER: ON = 128-255(51%-100%)
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	BAD BULB 145 ≤ value ≤ 162
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	INTENSITY
CH6/PARAMETER #3	SPEED
CH7/PARAMETER #4	N/A
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	FIREWORK 163 ≤ value ≤ 180
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	CCT SHIFT
CH6/PARAMETER #3	SPEED
CH7/PARAMETER #4	DECAY
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	EXPLOSION 181 ≤ value ≤ 198
CH4/PARAMETER #1	CCT
CH5/PARAMETER #2	DECAY
CH6/PARAMETER #3	TRIGGER: AUTO = 0-127(0%-50%) TRIGGER: MANUAL = 128-255(51%-100%)
CH7/PARAMETER #4	SPEED Trigger: OFF = 0-127(0%-50%) Trigger: ON = 128-255(51%-100%)
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

DMX EFFECT CHART

EFFECT	WELDING 199 ≤ value ≤ 216
CH4/PARAMETER #1	DIM LOW
CH5/PARAMETER #2	CCT
CH6/PARAMETER #3	SPEED
CH7/PARAMETER #4	PAUSE: OFF = 0-127(0%-50%) PAUSE: ON = 128-255(51%-100%)
CH8/PARAMETER #5	N/A
CH9/PARAMETER #6	N/A
CH10/PARAMETER #7	N/A

NANLITE

Guangdong NanGuang Photo&Video Systems Co.,Ltd.

☎ +86-754-85751187

☎ +86-754-85300887

✉ service@nanlite.com

<http://www.nanlite.com>

📍 Dongli Section, Highway 324, Chenghai, Shantou City, Guangdong Province, China